



Ronford-Baker

CAMERA SUPPORT TECHNOLOGY

Ronford-Baker Engineering Co. Ltd
Braziers, Oxhey Lane, Watford
Hertfordshire, WD19 5RJ, UK.

Tel: +44 (0)208 428 5941

Fax: +44 (0)208 428 4743

Email: info@ronfordbaker.co.uk

Web: www.ronfordbaker.co.uk

HEAVY DUTY TRIPOD



Ref. 10001

Head fittings

Mitchell top plate supplied as standard.
150mm bowl can be supplied on request.

Technical Specifications

Materials and Finish

Castings are LM25 anodised, stove enamelled black texture. Tubes are 1" dia x 16swg HE30TF alloy, polished and anodized, with nylon wipers and nylon locking pads. Stainless Steel spikes to feet, with rubber covers. Locking levers are anodized and stove enamelled black texture. All steel parts are hardened where necessary, and chrome plated.

Height

With legs spread at 1'6" (45.7cm): closed 3ft (91.4cm), fully extended 5'6" (167.6cm).

Weight

22lb (10kg).

Spreader

An infinitely adjustable spreader with a strong elastic clip-down device, which is secured in seconds. Made from high tensile anodized aluminium with large diameter locking hand-wheels to adjust length of spread; steel parts hardened and heavily chromium plated.

Dimensions (centre to foot) minimum 1'5" (43cm), maximum 2'1" (64cm).

Weight 4lb 7oz (2kg).

Baby Tripod

As above, but height range from 1'8" (50.8cm) to 3' (91.4cm)

Weight 18lb (8kg).

Transit Cases Specification

Moulded black grain AVS.

Dimensions 42" x 12" x 11" (105cm x 30cm x 27.5cm) standard.

26" x 12" x 11" (65cm x 30cm x 27.5cm) baby.

Weight 11lb (5kg) standard, 8lb (3.5kg) baby.



Ronford-Baker

CAMERA SUPPORT TECHNOLOGY

Ronford-Baker Engineering Co. Ltd
Braziers, Oxhey Lane, Watford
Hertfordshire, WD19 5RJ, UK.

Tel: +44 (0)208 428 5941

Fax: +44 (0)208 428 4743

Email: info@ronfordbaker.co.uk

Web: www.ronfordbaker.co.uk

MEDIUM DUTY TRIPOD



Ref. 10007

Head fittings

150cm bowl supplied as standard. Mitchell plate or 100cm bowl supplied to order.

Technical Specifications

Materials and Finish

Castings are LM25 anodised, stove enamelled black texture.

Tubes are $\frac{3}{4}$ " dia x 16swg HE30TF alloy, polished and anodised, with nylon wipers and nylon locking pads. Stainless Steel spikes to feet, with rubber covers.

Locking levers are anodised and stove enamelled black texture. All steel parts are hardened where necessary, and chrome plated.

Height

With legs spread at 1'6" (45.7cm): closed 3ft' (91.4cm), fully extended 5'6" (167.6cm).

Weight

14lb (6.5kg).

Spreader

An infinitely adjustable spreader, integral tripod, with a strong elastic clip-down device, which is secured in seconds. Made from high tensile anodised aluminium with large diameter locking hand-wheels to adjust length of spread; steel parts hardened and heavily chromium plated.

Dimensions (centre to foot) minimum 1'5" (43cm), maximum 2'1" (64cm).

Weight 4lb 7oz (2kg).

Baby Tripod

As above, but height range from 1'8" (50.8cm) to 3' (91.4cm) Weight 11lb (5kg).

Transit Cases Specification

Moulded black grain AVS. Dimensions 42" x 12" x 11" (105cm x 30cm x 27.5cm) standard. 26" x 12" x 11" (65cm x 30cm x 27.5cm) baby. Weight 11lb (5kg) standard, 6lb (2.7kg) baby.



Ronford-Baker

CAMERA SUPPORT TECHNOLOGY

Ronford-Baker Engineering Co. Ltd
Braziers, Oxhey Lane, Watford
Hertfordshire, WD19 5RJ, UK.

Tel: +44 (0)208 428 5941

Fax: +44 (0)208 428 4743

Email: info@ronfordbaker.co.uk

Web: www.ronfordbaker.co.uk

LIGHTWEIGHT TRIPOD



Ref. 10013

Head fittings

150cm bowl supplied as standard. Mitchell plate or 100cm bowl supplied to order.

Technical Specifications

Materials and Finish

Castings are LM25 anodised, stove enamelled black texture.

Tubes are 5/8" dia x 16swg HE30TF alloy, polished and anodised, with nylon wipers and nylon locking pads.

Stainless Steel spikes to feet, with rubber covers.

Locking levers are anodised and stove enamelled black texture. All steel parts are hardened where necessary, and chrome plated.

Height

With legs spread at 1'6" (45.7cm): closed 3ft (91.4cm), fully extended 5'6" (167.6cm).

Weight

7lb (3.1kg).

Spreader

An infinitely adjustable spreader, integral tripod, with a strong elastic clip-down device, which is secured in seconds. Made from high tensile anodised aluminium with large diameter locking hand-wheels to adjust length of spread; steel parts hardened and heavily chromium plated.

Dimensions (centre to foot) minimum 1'5" (43cm), maximum 2'1" (64cm).

Weight 4lb 7oz (2kg).

Baby Tripod

As above, but height range from 1'8" (50.8cm) to 3' (91.4cm) Weight 5lb (2.3kg).

Transit Cases Specification

Moulded black grain AVS. Dimensions 42" x 12" x 11" (105cm x 30cm x 27.5cm) standard. 26" x 12" x 11" (65cm x 30cm x 27.5cm) baby.

Weight 11lb (5kg) standard, 6lb (2.7kg) baby.



Ronford-Baker

CAMERA SUPPORT TECHNOLOGY

Ronford-Baker Engineering Co. Ltd
Braziers, Oxhey Lane, Watford
Hertfordshire, WD19 5RJ, UK.

Tel: +44 (0)208 428 5941

Fax: +44 (0)208 428 4743

Email: info@ronfordbaker.co.uk

Web: www.ronfordbaker.co.uk

2 STAGE TRIPODS

LIGHTWEIGHT

Head fittings
150m/m or 100m/m bowl

Height on spreader
maximum 67¹/₂" (171cm)

Minimum 19" (48cm)

Weight 11lb (5kg)



Ref. 10015

MEDIUM DUTY

Head fittings
Mitchell/150m/m bowl
or 100m/m bowl

Height on spreader
maximum 67" (170cm)

Minimum 20" (51cm)

Weight 17lb (8kg)



Ref. 10003

HEAVY DUTY

Head fittings
Mitchell or 150m/m bowl

Height on spreader
maximum 67" (170cm)

Minimum 19" (48cm)

Weight 30lb (14kg)



Ref.10003



Ronford-Baker

CAMERA SUPPORT TECHNOLOGY

Ronford-Baker Engineering Co. Ltd
Braziers, Oxhey Lane, Watford
Hertfordshire, WD19 5RJ, UK.

Tel: +44 (0)208 428 5941

Fax: +44 (0)208 428 4743

Email: info@ronfordbaker.co.uk

Web: www.ronfordbaker.co.uk

LOW ANGLE TRIPOD



Ref. 10019 (with case)

Head castings

150cm or 100mm bowl. Other fittings can be supplied on request.

Stirrup Casings

Pivot from head and terminate in very efficient nylon cam clamps operated by large diameter hand wheels, make the changeover from one set of legs to another a matter of seconds. The combination of legs covers any height from floor to 2' 11" (88.9cm).

Technical Specifications

Materials

Manufactured from LM25 alloy castings and high tensile alloy tube.

Finish

Castings are anodised and stove enamelled black texture. Tubes are polished and satin anodised. Steel parts are chromium plated. Tie down points are provided on head and bottom of telescopic legs.

Height

Low angle 7 1/2" (19.5cm). Stub legs 13 1/2" (34.29cm).

Telescopic legs max. 2' 11" (88.9cm), min 2' (60.98cm).

Net Weight

Head and stirrups only 5lb 2oz (2.32kg)

Steel Feet 14oz (0.39kg)

Stub legs 12oz (0.34kg)

Telescopic legs 3lb 4oz (1.47kg)

Limpets 6lb 10oz (3kg)

Total weight 10lb (4.5kg)

Transit Cases Specification

Rigidised aluminium.

Dimensions 21 1/4" x 13 1/4" x 10 1/4" (54cm x 37cm x 26cm) standard. 26" x 12" x 11" (65cm x 30cm x 27.5cm) baby.

Weight 14lb (6kg).



Ronford-Baker
CAMERA SUPPORT TECHNOLOGY

Ronford-Baker Engineering Co. Ltd
Braziers, Oxhey Lane, Watford
Hertfordshire, WD19 5RJ, UK.

Tel: +44 (0)208 428 5941

Fax: +44 (0)208 428 4743

Email: info@ronfordbaker.co.uk

Web: www.ronfordbaker.co.uk

TRIPOD SPREADERS



Spreaders



Ronford-Baker

CAMERA SUPPORT TECHNOLOGY

Ronford-Baker Engineering Co. Ltd
Braziers, Oxhey Lane, Watford
Hertfordshire, WD19 5RJ, UK.

Tel: +44 (0)208 428 5941

Fax: +44 (0)208 428 4743

Email: info@ronfordbaker.co.uk

Web: www.ronfordbaker.co.uk

TRIPOD HEIGHT & WEIGHT TABLE

Type of Tripod	Max. Height	Min. Height	Weight of Tripod with Aluminium Tubes	Weight of Tripod with Carbon Fibre Tubes
Heavy Duty Tall	68" (173cm)	35" (89cm)	22lbs 10kgs	
Heavy Duty Short	33½" (85cm)	10" (25cm)	18lbs 8.18kgs	
Heavy Duty Reverse Leg	65" (165cm)	35" (89cm)	25lbs 11.36kgs	
Heavy Duty 2 Stage	68" (165cm)	22½" (57cm)	30lbs 13.64kgs	
Medium Duty Tall	70" (178cm)	34" (86cm)	14lbs 6.36kgs	12lbs 5.45kgs
Medium Duty Short	36" (91cm)	7" (18cm)	11lbs 5.0kgs	9.5lbs 4.3kgs
Medium Duty Reverse Leg	49" (125cm)	24" (61cm)	12lbs 5.45kgs	
Medium Duty 2 Stage	64" (163cm)	19" (48cm)	17lbs 7.73kgs	14lbs 6.3kgs
Lightweight Tall	70" (178cm)	34" (86cm)	7lbs 3.18kgs	4.4lbs 2kgs
Lightweight Short	33" (84cm)	7" (18cm)	5lbs 2.27kgs	3.5lbs 1.6kgs
Lightweight Reverse Leg	48" (122cm)	22½" (57cm)	7lbs 3.18kgs	
Lightweight 2 Stage	62½" (159cm)	19" (48cm)	11lbs 5.0kgs	9lbs 4.09kgs

N.B These Heights are measured on a spreader.

Maximum & Minimum heights can usually be supplied to customer's individual specification.